

NC 7.5 Compressor

- ❖ 9 CFM
- ❖ 6000 PSI
- ❖ 7.5 HP electric motor
- ❖ Single or three phase electric
- ❖ 39" h. x 29" d. x 44" h.
- ❖ Weight: 500 lbs. approx.



SPECIFICATIONS

COMPRESSOR

The compressor block is 4 stage, air cooled, pressure lubricated, has inter coolers and after cooler, relief valves on all stages, and a multi-blade flywheel fan to provide high velocity cooling over the compressor. Standard equipment includes an auto-drain system, inner stage gauges, hour meter, high pressure shut down, carbon-monoxide visual indicator and a deluxe 3-sided enclosure including a gauge panel.

PURIFICATION

The filtration system consists of one chamber designed to operate at 6000 PSI with a 4:1 safety factor. It is rated at 40,000 cu. ft. of air capacity. The system uses a dryer bed to remove water in excess of dew point -65 degrees. (NFPA 1500 standard) Activated charcoal and a carbon monoxide catalyst remove remaining contaminants to provide CGA Grade "E" breathing air. Additional filtration capacity can added for high volume users.

ELECTRICAL REQUIREMENTS

The minimum requirement for single-phase operation is a 50 Amp, 230 Volt connection. The minimum requirement for three-phase operation is a 40 Amp, 230 or 208 Volt connection.

North Shore Compressor & Machine, Inc

83 Outer Drive, Silver Bay, MN 55614 (218) 226-4695 Voice

(218)-226-3440 Fax

www.northshorecompressor.com

email: info@northshorecompressor.com