

Model Number	CFM	Driver	Phase	HP	PSI	Stages	Filter Capacity @ 80 degrees	Filter #	Estimated Hours before filter change at 80 degrees	Magnetic Starter	Manual Drain System	Auto Drain	CO- Moisture Indicator	Gauge Panel	High Pressure Switch	Electrical 208/230 V 60 Hertz	RPM	Cabinet Style	Dimensions L" x W" x H"	Weight	Printable Flyer (Needs Acrobat Reader)	
O3-9G-A	9	Gas	Single	9	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	18 hours - Option 44 hours	No	Standard	No	No	No	No	N/A	1000	Open w/ guards	42 x 24 x 26	350 lbs	O3-9G-A Compressor	
O3-5-A1	6.5	Electric	Single	5	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	25 hours - Option 80 hours	Optional	Standard	Optional	Optional	No	Optional	30 amp	1000	Open w/ guards	53 x 21 x 30	320 lbs	O3-5-A1 Compressor	
O3-5-A3	6.5	Electric	Three	5	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	25 hours - Option 80 hours	Optional	Standard	Optional	Optional	No	Optional	30 amp	1000	Open w/ guards	53 x 21 x 30	320 lbs	O3-5-A3 Compressor	
O3-7.5-A1	9	Electric	Single	7.5	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	18 hours - Option 53 hours	Optional	Standard	Optional	Optional	No	Optional	40 amp	1350	Open w/ guards	53 x 21 x 30	330 lbs	O3-7.5-A1 Compressor	
O3-7.5-A3	9	Electric	Three	7.5	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	18 hours - Option 53 hours	Optional	Standard	Optional	Optional	No	Optional	30 amp	1350	Open w/ guards	53 x 21 x 30	330 lbs	O3-7.5-A3 Compressor	
E3-5-A1	6.5	Electric	Single	5	5000	3	24,000cf optional 57,000 cf	X65247 Option X65677	61 hours - Option 146 hours	Standard	No	Standard	Standard	Standard	Standard	Standard	30 amp	1000	Enclosed	39 x 29 x44	550 lbs	E3-5-A1 Compressor
E3-5-A3	6.5	Electric	Three	5	5000	3	24,000cf optional 57,000 cf	X65247 Option X65677	61 hours - Option 146 hours	Standard	No	Standard	Standard	Standard	Standard	Standard	30 amp	1000	Enclosed	39 x 29 x44	550 lbs	E3-5-A3 Compressor
E3-7.5-A1	9	Electric	Single	7.5	5000	3	24,000cf optional 57,000 cf	X65247 Option X65677	44 hours - Option 105 hours	Standard	No	Standard	Standard	Standard	Standard	Standard	40 amp	1350	Enclosed	39 x 29 x44	550 lbs	E3-7.5-A1 Compressor
E3-7.5-A3	9	Electric	Three	7.5	5000	3	24,000cf optional 57,000 cf	X65247 Option X65677	44 hours - Option 105 hours	Standard	No	Standard	Standard	Standard	Standard	Standard	30 amp	1350	Enclosed	39 x 29 x44	550 lbs	E3-7.5-A3 Compressor