

Model Number	CFM	Driver	Phase	HP	PSI	Stages	Filter Capacity @ 80 degrees	Filter #	Estimated Hours before filter change at 80 degrees	Magnetic Starter	Manual Drain System	Auto Drain	CO-Moisture Indicator	Gauge Panel	High Pressure Switch	Electrical 208/230 V 60 Hertz	RPM	Cabinet	Dimensions w" x d" x h"	Weight	Printable Flyer (Needs Acrobat Reader)
E4-7.5-N-E1	9	Electric	Single	7.5	6000	4	24,000cf optional 57,000 cf	X65247 Option X65677	44 hours - Option 105 hours	Standard	No	Standard	Standard	Standard	Standard	40 amp	1100	Enclosed	39 x 29 x44	550 lbs	E4-7.5-N-E1 Compressor
E4-7.5-N-E3	9	Electric	Three	7.5	6000	4	24,000cf optional 57,000 cf	X65247 Option X65677	44 hours - Option 105 hours	Standard	No	Standard	Standard	Standard	Standard	30 amp	1100	Enclosed	39 x 29 x44	550 lbs	E4-7.5-N-E3 Compressor
E4-10-N-E1	14	Electric	Single	10	6000	4	24,000cf optional 57,000 cf	X65247 Option X65677	28 hours - Option 67 hours	Standard	No	Standard	Standard	Standard	Standard	50amp	1400	Enclosed	39 x 29 x44	600 lbs	E4-10-N-E1 Compressor
E4-10-N-E3	14	Electric	Three	10	6000	4	24,000cf optional 57,000 cf	X65247 Option X65677	28 hours - Option 67 hours	Standard	No	Standard	Standard	Standard	Standard	40amp	1400	Enclosed	39 x 29 x44	600 lbs	E4-10-N-E3 Compressor
E4-15-C-E3	21	Electric	Three	15	6000	4	57,000 cf	X65247/X65677	45 hours	Standard	No	Standard	Standard	Standard	Standard	50 amp	1100	Enclosed	46 x 29 x 45	900 lbs	E4-15-C-E3 Compressor
E4-20-C-E3	24	Electric	Three	20	6000	4	57,000 cf	X65247/X65677	39 hours	Standard	No	Standard	Standard	Standard	Standard	60 amp	1250	Enclosed	46 x 29 x 45	900 lbs	E4-20-C-E3 Compressor
O4-20-CE3 Industrial	24	Electric	Three	20	6000	4	57,000 cf	X65247/X65677	39 hours	Standard	No	Standard	Standard	Standard	Standard	60 amp	1250	Open w/ guards	57 x 34 x 35	850 lbs	O4-20-C-E3 Ind. Compressor
N15-1000 E3	30	Electric	Three	15	1000	3	Optional	Optional	Optional	Standard	Standard	Optional	Standard	No	Standard	50 amp	850	Open w/ guards	33 x 29 x 60	1200 lbs	N15-1000

