

Model Number	CFM	Driver	Phase	HP	PSI	Stages	Filter Capacity @ 80 degrees	Filter #	Estimated Hours before filter change at 80 degrees	Magnetic Starter	Manual Drain System	Auto Drain	CO-Moisture Indicator	Gauge Panel	High Pressure Switch	Electrical 208/230 V 60 Hertz	RPM	Cabinet Style	Dimensions L" x W" x H"	Weight
NA-G	3.5	Gas	Single	6	4700	4	3,000 cf	X-N-ATL	17 hours	No	Standard	No	No	No	No	N/A	2300	Open w/ guards	29 X 16.5 X 16	90 lbs
NA-E1	3.5	Electric	Single	3	4700	4	3,000 cf	X-N-ATL	17 hours	No	Standard	No	No	No	No	30 amp	2300	Open w/ guards	23 X 16.5 X 16	87 lbs
O3-G	9	Gas	Single	9	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	18 hours - Option 44 hours	No	Standard	No	No	No	No	N/A	1000	Open w/ guards	42 x 24 x 26	350 lbs
O3-5-A1	6.5	Electric	Single	5	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	25 hours - Option 80 hours	Optional	Standard	Optional	Optional	No	Optional	30 amp	1100	Open w/ guards	53 x 21 x 30	320 lbs
O3-5-A3	6.5	Electric	Three	5	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	25 hours - Option 80 hours	Optional	Standard	Optional	Optional	No	Optional	30 amp	1100	Open w/ guards	53 x 21 x 30	320 lbs
O3-7.5-A1	9	Electric	Single	7.5	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	18 hours - Option 53 hours	Optional	Standard	Optional	Optional	No	Optional	40 amp	1500	Open w/ guards	53 x 21 x 30	330 lbs
O3-7.5-A3	9	Electric	Three	7.5	5000	3	9,800 cf optional 24,000 cf	X65240 Option X65247	18 hours - Option 53 hours	Optional	Standard	Optional	Optional	No	Optional	30 amp	1500	Open w/ guards	53 x 21 x 30	330 lbs
E3-5-A1	6.5	Electric	Single	5	5000	3	24,000cf optional 57,000 cf	X65247 Option X65677	61 hours - Option 146 hours	Standard	No	Standard	Standard	Standard	Standard	30 amp	1000	Enclosed	39 x 29 x44	600 lbs
E3-5-A3	6.5	Electric	Three	5	5000	3	24,000cf optional 57,000 cf	X65247 Option X65677	61 hours - Option 146 hours	Standard	No	Standard	Standard	Standard	Standard	30 amp	1000	Enclosed	39 x 29 x44	600 lbs
E3-7.5-A1	9	Electric	Single	7.5	5000	3	24,000cf optional 57,000 cf	X65247 Option X65677	44 hours - Option 105 hours	Standard	No	Standard	Standard	Standard	Standard	40 amp	1500	Enclosed	39 x 29 x44	600 lbs
E3-7.5-A3	9	Electric	Three	7.5	5000	3	24,000cf optional 57,000 cf	X65247 Option X65677	44 hours - Option 105 hours	Standard	No	Standard	Standard	Standard	Standard	30 amp	1500	Enclosed	39 x 29 x44	600 lbs
E4-7.5-N-E1	9	Electric	Single	7.5	6000	4	24,000cf optional 57,000 cf	X65247 Option X65677	44 hours - Option 105 hours	Standard	No	Standard	Standard	Standard	Standard	40 amp	1100	Enclosed	39 x 29 x44	650 lbs
E4-7.5-N-E3	9	Electric	Three	7.5	6000	4	24,000cf optional 57,000 cf	X65247 Option X65677	44 hours - Option 105 hours	Standard	No	Standard	Standard	Standard	Standard	30 amp	1100	Enclosed	39 x 29 x44	650 lbs
E4-10-N-E1	14	Electric	Single	10	6000	4	24,000cf optional 57,000 cf	X65247 Option X65677	28 hours - Option 67 hours	Standard	No	Standard	Standard	Standard	Standard	50amp	1400	Enclosed	39 x 29 x44	700 lbs
E4-10-N-E3	14	Electric	Three	10	6000	4	24,000cf optional 57,000 cf	X65247 Option X65677	28 hours - Option 67 hours	Standard	No	Standard	Standard	Standard	Standard	40amp	1400	Enclosed	39 x 29 x44	700 lbs
E4-15-C-E3	21	Electric	Three	15	6000	4	57,000 cf	X65247/X65677	45 hours	Standard	No	Standard	Standard	Standard	Standard	50 amp	1100	Enclosed	46 x 29 x 45	900 lbs
E4-20-C-E3	24	Electric	Three	20	6000	4	57,000 cf	X65247/X65677	39 hours	Standard	No	Standard	Standard	Standard	Standard	60 amp	1250	Enclosed	46 x 29 x 45	1100 lbs
O4-20-C-E3 Industrial	24	Electric	Three	20	6000	4	57,000 cf	X65247/X65677	39 hours	Standard	No	Standard	Standard	Standard	Standard	60 amp	1250	Open w/ guards	57 x 34 x 35	1200 lbs
N15-1000 E3	30	Electric	Three	15	1000	3	Optional	Optional	Optional	Standard	Standard	Optional	Standard	No	Standard	50 amp	850	Open w/ guards	33 x 29 x 60	1200 lbs