

# ***NP-G Air Compressor***



- ❖ 6 or 9 CFM
- ❖ 5000 PSI
- ❖ 6.5 or 9 HP
- ❖ 42" W x 24" D  
x 36" H
- ❖ Approx. 350  
lbs.

## **SPECIFICATIONS**

### **COMPRESSOR**

The compressor block is 3 stage, air cooled, has intercoolers and aftercooler, relief valves on all stages, and a multi-blade fly wheel to provide high velocity cooling over the compressor. The compressor has manual drains for condensate.

### **PURIFICATION**

An 8,000 Cu. Ft. filtration system is designed to operate at 5000-PSI working pressure with a 4:1 safety factor. The system uses a dryer bed to remove water in excess of dew point -65 degrees. (NFPA 1500 standard) Activated charcoal and a carbon monoxide catalyst remove remaining contaminants to provide CGA Grade "E" breathing air. Additional filtration capacity can be added for high volume users.

### **GASOLINE DRIVEN**

This unit is driven by a 6.5 or 9 horse power Honda engine.  
An upgrade to diesel is available.  
(Pictured with diesel engine)

### **North Shore Compressor & Machine, Inc**

83 Outer Drive, Silver Bay, MN 55614 (218) 226-4695 (218)-226-3440 Fax  
[www.northshorecompressor.com](http://www.northshorecompressor.com) email: info@northshorecompressor.com