



NORTH SHORE
COMPRESSOR & MACHINE, INC.

E4-7.5-A6 Compressor

Made In The USA



- ❖ 6000 PSI
- ❖ 10 CFM
- ❖ 7.5 HP electric motor
- ❖ Single or three phase electric
- ❖ 66.75" h. x 23" d. x 36" w.
- ❖ Weight: ~600 lbs. approx.



SPECIFICATIONS

COMPRESSOR

The compressor block is 4 stage, air cooled, splash lubricated, has inter coolers and after cooler, relief valves on all stages, and a multi-blade flywheel fan to provide high velocity cooling over the compressor. Standard equipment includes an auto-drain system, inner stage gauges, hour meter, high pressure shut down, carbon-monoxide visual indicator and a fully enclosed, sound dampened cabinet with gauge panel.

PURIFICATION

The filtration system consists of one chamber rated at 24,000 cu. ft. of air capacity at 80 degrees. The system uses a dryer bed to remove water in excess of dew point -65 degrees. (NFPA 1500 standard) Activated charcoal and a carbon monoxide catalyst remove remaining contaminants to provide CGA Grade "E" breathing air. Additional filtration capacity can added for high volume users.

ELECTRICAL REQUIREMENTS

The minimum requirement for single-phase operation is a 40 Amp, 230 Volt connection.
The minimum requirement for three-phase operation is a 30 Amp, 230 or 208 Volt connection.

North Shore Compressor & Machine, Inc

83 Outer Drive, Silver Bay, MN 55614
www.northshorecompressor.com

(218) 226-4695 Voice

(218)-226-3440 Fax

email: info@northshorecompressor.com