



NORTH SHORE
COMPRESSOR & MACHINE, INC.

N15-1000 PSI Industrial **Compressor**

- ❖ 1000 PSI
- ❖ 15 HP ELECTRIC MOTOR
- ❖ 30 CFM
- ❖ Three Phase Electric
- ❖ Approx. - 33" H x 29"W x 60"L
- ❖ Weight: 1,200 lbs. approx.



Optional Filtration System not pictured

SPECIFICATIONS

COMPRESSOR

The compressor block is 3 stage, air cooled, splash lubricated, has inter coolers and after cooler, relief valves on all stages, and a multi-blade flywheel fan to provide high velocity cooling over the compressor. Standard equipment includes a manual drain system (auto-drain system is optional), hour meter, high-pressure shut down, and all protective guards.

OPTIONAL PURIFICATION

The optional filtration system consists of two chambers designed to operate at 1000 PSI with a 4:1 safety factor. It comes with a two cartridge filtration system rated at 100,000 Cu. Ft. of air capacity at 68°F. The system uses a dryer bed to remove water in excess of dew point -65 degrees. (NFPA 1500 standard) This purification system is designed to be wall mounted near the compressor.

ELECTRICAL REQUIREMENTS

The minimum requirement for three-phase operation is a 50 Amp, 230 or 208 Volt connection.

North Shore Compressor & Machine, Inc

83 Outer Drive, Silver Bay, MN 55614 (218) 226-4695

www.northshorecompressor.com

800-526-6395

(218)-226-3440 Fax

email: info@northshorecompressor.com