

CLASS II CONTAINMENT FILL STATIONS



- ❖ Available in one, two, or three positions
- ❖ Manual locking bar for safety
- ❖ One inlet connector from cascade
- ❖ Fill hoses include bleed valve and SCBA fill adapters
- ❖ Teflon slides to protect from scuffing
- ❖ Venting at back and bottom for operator safety



Optional Control Panel

Same as above plus the following:

4 Bank Controls

- ❖ 4-2 ½" Bank Gauges
- ❖ 1-4" Result Gauge
- ❖ 0-6000 PSI input, 0-5000 PSI output adjustable regulator
- ❖ 4 inlet connectors from cascades
- ❖ 1 inlet connection for compressor
- ❖ 1 auxiliary outlet with valve



Size	Standard	With Controls
Single Position	21" W x 23" D x 41" H	21" W x 23" D x 56" H
Two Position	30" W x 24" D x 41" H	30" W x 24" D x 55" H
Three Position	42" W x 24" D x 41" H	42" W x 24" D x 55" H

North Shore Compressor & Machine, Inc

83 Outer Drive, Silver Bay, MN 55614 (218) 226-4695 Voice (218)-226-3440 Fax

www.northshorecompressor.com

email: info@northshorecompressor.com

800-526-6395